

## HEAT SHRINK INDOOR TERMINATION KIT – MONOi

**Nexans MONO** type MV cable terminations are Mono Heat Shrink Outdoor Termination Kit consisting of a **Single-piece Heat Shrink Tube – the Anti tracking tube**. It features **Integral Stress Control** co-extruded into the heat shrink tubing suitable for terminating 1 core & 3 core polymeric insulated cables, such as XLPE or EPR, with working voltage classes of up to 36 kV.

Cable

XLPE / PVC

PILC

KV

1.1 kV

3.3 kV

6.6 kV

11 kV

22 kV

33 kV

Core

1 Core

2 Core

3 Core

3.5 / 4 Core

4 - 35

50 - 120

150 - 240

300 - 400

500 - 630

800 - 1000

Call Me Back



Cable Size (Sq.  
Mm)

1

Add to quote

Categories: CABLE ACCESSORIES, CABLE JOINTING & TERMINATION KITS Tags: Heat Shrink Indoor Termination, Heat Shrink Termination, Indoor Termination Kit, Mono Heat Shrink Termination

Description

Additional information

Document

Reviews (0)

Description

The “MONOi” indoor terminations are designed for max system voltages of 36 kV, for compact switchgears as well as for installations where space is limited. Easy, quick to install, reducing installation time and errors.

The kit consists of a stress control mastic strip, a co extruded dual wall tube and red anti-tracking sealing mastic.

**MONOi 1C Dimensions:**



**MONO SC Dimensions:**

---

Related products

**T SHAPED SCREENED  
SEPARABLE COUPLING  
CONNECTORS**

Select options

**HEAT SHRINK RIGHT  
ANGLE BOOTS**

Select options


**HEAT SHRINK SPREADER  
CAPS/ BREAKOUTS (RED &  
BLACK)**


Select options


**TINNED COPPER BRAIDS**

Select options

## Reach Us

 25, Shah Industrial Estate,  
Kotambi, Vadodara, Gujarat –  
391510

 +91-7574806580

 02668-299156

## Our Company

About Company

Privacy Policy

Terms of Use

Our Solutions

Blogs

## Quick Links

Medium Voltage Cable Accessories

Cable Termination

Cable Jointing kit

## Recent Post

May 4, 2020

Shear Bolt Lugs &

Connectors

October 11, 2020

